

LF Aftershock Siren System

Introducing Aftershock, SoundOff Signal's first low frequency siren system for emergency vehicles. Aftershock's low frequency sound waves produce deep warning tones, proven highly effective in traffic clearing. Ideal for high traffic areas and busy intersections, Aftershock is available with one or two speakers to meet your specific needs. Universal brackets included.



Siren System, Includes Universal Bracket

100 Watt Speaker, 200 Watt Amplifier

ETSKLF1ØØ

Two (2) 100 Watt Speakers, 200 Watt Amplifier

ETSKLF2ØØ

Speaker, Includes Universal Bracket

Low Frequency Speaker, 100 Watt

ETSSLF1ØØ

WATTS 100 Watts with 1 speaker or 200 Watts with 2 speakers

INPUT VOLTAGE 10-16 Vdc

OPERATING TEMPERATURE -40° C to +65° C

CURRENT DRAW 8 Amps at 100 Watts and 16 Amps at 200 Watts

OUTPUT VOLTAGE 58-64 Vpk-pk

DIMENSIONS

Siren

Height 2.4" (6 cm)

Width 4.7" (11.9 cm)

Depth 5" (12.7 cm)

Speaker

Height 8.5" (21.6 cm)

Diameter 7.2" (18.4 cm)

WARRANTY Three-year

Contact your sales representative for additional information.